



Landau Bar/Nameplate Maintenance Tips

- We highly recommend periodically tightening the acorn nuts. To ensure they do not get overtightened, we recommend finger tightening them.
- **Washing your vehicle:**
 - **ALWAYS** remove your landau bar before going through an automatic car wash
 - Brush Car Washers - Will catch on your fasteners and break the Landau Bars or Nameplates loose.
- Removal of black fasteners (bolts) - **DO NOT PULL**, use a 5/16" wrench and turn them clockwise or counter clockwise to pop them off. Then clean any residue left on the glass with a new razor blade. When it comes time to reinstall, you will need to order new fasteners (bolts).
 - Reinstalling: to ensure proper adhesion of mastic tape on the base of the fastener, the glass area should be at least 65 degrees. After cleaning the window we recommend using a heat gun or hair dryer to warm the glass.
- Landau bar care for those in salt-air or that experience winters with salt on the roads, we recommend removing your bars twice a year and waxing them.
- **Should a stud ever come loose from the glass, it is highly recommended to NOT operate the vehicle until the landau bar is removed or replaced.**

Have a question or comment? Email us at gburnsllc@gmail.com or call us at 937-210-4805.

Share a photo of your landau bar, nameplate, or any other G. Burns product to gburnsllc@gmail.com